

TECHNICAL DATA

THE 12 Be PRO

PASSIVE

WEDGE



Speaker Type	12" Beryllium dome, time-coherent point-source coaxial
Principle	Vented
Passive Active	Passive
Woofer	12" woofer
Tweeter	3" voice coil diameter, Beryllium dome compression driver
Recommended ASCENDO Amplifiers	AIA2-2704, AIA2-6004, AIA4-2404, AIA4-6004, AIA8-6004
SPL (Peak / half space 2pi)	Calculated Data 123 dB (Cont.) / 135 dB (Peak) 118 dB @ 60 Hz 100 dB @ 40 Hz
Frequency Range	Calculated Data 75 Hz - 21 kHz / -3dB
Efficiency	91 dB / 1W/1m 4 pi, 97 dB / 1W/m 2 p
Power Handling	900W
Impedance	8 Ω
Directivity Horizontal x Vertical in deg°	85° x 85°
Input Terminal	Neutrik Speakon

Enclosure	Internally braced birch ply and MDF
Dimensions (W/H/D)mm (Without grille)	500 312 450 (Vertical) 500 450 312 (Horizontal)
Dimensions (W/H/D)inch (Without grille)	19 11/16 17 11/16 12 5/16 (Vertical) 19 11/16 12 5/16 17 11/16 (Horizontal)
Packing Dimensions (W/H/D)mm	590 430 550
Packing Dimensions (W/H/D)inch	23 4/16 16 15/16 21 10/16
Weight	46.29 lbs 21.0 kg
Gross Weight	55.12 lbs 25.0 kg
Finish	Structural paint black
Mounting	4 x wall brackets for horizontal and vertical installation, VESA 200 x 200 mounting option

The THE12 Be PRO PASSIVE WEDGE is supplied with a front cover as standard



Technical modifications subject to change without further notice | Technische Änderungen vorbehalten