

TECHNICAL DATA

THE 5 PASSIVE ON WALL

Ascendo
ELEVATE YOUR SOUND



Speaker Type	5 1/4" time-coherent point-source coaxial
Principle	Vented
Passive Active	Passive
Woofer	5 1/4" woofer
Tweeter	1" soft dome
Recommended ASCENDO Amplifiers	AIA2-1404, AIA4-2404, AIA8-2704, AIA8-6004
SPL (Peak / half space 2pi)	Measured Data 108 dB (Cont.) / 120 dB (Peak)
Frequency Range	Measured Data (Without DSP) 100 Hz - 20 kHz / -3dB
Efficiency	83 dB / 1 W/m 4 pi, 89 dB / 1 W/m 2 pi
Power Handling	100 W
Impedance	8 Ω
Directivity Horizontal x Vertical in deg°	85° x 85°
Input Terminal	4-conductor Phoenix 12 AWG (3.3 mm²)



Enclosure	Internally braced MDF
Dimensions (W/H/D)mm (Without grille)	250 400 75 (With grille: 81)
Dimensions (W/H/D)inch (Without grille)	9 13/16 15 3/4 2 15/16 (With grille: 3 3/16)
Packing Dimensions (W/H/D)mm	360 500 180
Packing Dimensions (W/H/D)inch	14 3/16 19 11/16 7 1/16
Weight	8.82 lbs 4.0 kg
Gross Weight	12.13 lbs 5.5 kg
Finish	Matte black / White glossy
Mounting	4 x wall brackets for horizontal and vertical installation, 2 through-holes for direct wall or ceiling mounting, VESA 100 x mounting points

The THE5 PASSIVE ON WALL is supplied with a front cover as standard



Technical modifications subject to change without further notice | Technische Änderungen vorbehalten