

Ascendo

ELEVATE YOUR SOUND

AIA8-2704



DATA SHEET

AUDIO

Table 1. **Inputs**

Channels	8
Signal-to-Noise Ratio	104 dB
Sensitivity	1.1 V

Table 1. **Outputs**

Output Power	230 V @ 4 Ω	230 V @ 8 Ω	Bridged: 230 V @ 8 Ω
	8 x 340 W	8 x 225 W	4 x 680 W
Frequency response	20 Hz – 20 kHz		
Protection	Soft-start, Turn-on Turn-off transients, Over-heating, DC, RF, Short-circuit, Open or mismatched loads, ICL™, PMST™		
Damping factor	>400		
Total Harmonic Distortion	<0.05 %		
Intermodulation Distortion	<0.05 %		
Crosstalk 20Hz – 1kHz	>75 dB		
Voltage Gain	32 dB		

AC MAINS POWER

Operating Voltage	170 - 265 VAC 90 - 140 VAC (opt.)
Power On Idling (@230V)	0.5 A
1/8 Rated Power (230V @ 4Ω)	4 A

CONNECTORS



Figure 1. AIA8-2704 connectors

Audio signal input connectors	Neutrik XLR
Audio signal output connectors	Neutrik XLR
Speaker connector	Neutrik speakON®

THERMAL

Thermal dissipation	Fan, variable speed, temperature controlled front to rear airflow			
	230 VAC		120 VAC	
idle	216 BTU/h	54 kcal/h	216 BTU/h	54 kcal/h
1/8 power @ 8Ω	230 BTU/h	58 kcal/h	230 BTU/h	58 kcal/h
1/8 power @ 4Ω	272 BTU/h	69 kcal/h	272 BTU/h	69 kcal/h

USER INTERFACES

Hardware	Status LEDs, Potentiometers, Power button
----------	---

DIMENSIONS / WEIGHT




Figure 2. AIA8-2704 dimensions

Dimensions (W/H/D) mm	483 89 416 (2RU)
Dimensions (W/H/D) Inch	19 3 1/2 16 3/8 (2RU)
Packing Dimensions W/H/D) mm	650 270 600
Packing Dimensions (W/H/D) inch	25 9/16 10 5/8 23 5/8
Weight	18.74 lbs 8.5 kg
Gross Weight	27.56 lbs 12.5 kg



CE



Tel.: +49 9872-9 537 157 · www.aia-cinema.com

